

AiOx—Audio in out—eXtended.—Following on from the original AiO is AiOx.

A redesign of the standard transformer balanced interface system. The Clip LEDs of before are still there and we now have a single, signal present, blue LED to show if either of the input has a signal on exceeding about 30dB,

The output has a similar system where the Power on LED glows to the peaks of the output Audio.

Main Features

- ✓ USB powered
- ✓ Earth Lift
- ✓ Variable Output Level control
- ✓ Line or Mic level inputs with independent controls
- ✓ Signal Preset and Clip LEDs
- ✓ Transformer balancing on input and output.

3 Year Limited Factory Warranty

Specifications

Power

USB powered

Signals

USB 2.0

Audio line 0dB out

Audio in 0dB and Mic -40dB

Bandwidth 20Hz—20kHz

Connections:

USB B from host computer

2 x XLR male out

2 x XLR female in

Dimensions mm (inch)

D x W x H

D x W x H 95 (3 3/4") x 125 (4 15/16") x 50 (2")

Weight each

256g (9oz)

Note XLR cables and not included as standard.

Interspace Industries

Unit 1F Tewin Court, Tewin Road, Welwyn Garden City, Hertfordshire, AL7 1AU, UK

call: +44 (0) 1462 600 101 email: moreinfo@interspaceind.com web: www.interspaceind.com

Disclaimer: Whilst all care is taken to ensure accuracy, Interspace Industries Ltd accepts no responsibility for any errors or omissions, whether implied or otherwise interpreted. All specifications subject to change without notice.



Simple Audio to USB interfacing



Accessories

USB cable

