

# USB Bal Box<sup>2</sup>

**USB Balance Box<sup>2</sup>** eliminates hum problems when connecting audio from your presentation computer source. Hum can happen anywhere, you don't have to be running your audio signal a long distance. Power supplies, fluorescent lights and all sorts of equipment can cause noise that is picked up by your audio input cables.

The USB Bal box is a self-contained sound card therefore bypassing the internal DAC of the host machine providing a clean sound without pre-emphasis that can be used on headphone drives.

This Version 2 has new transformers for better bandwidth and clarity - beautiful and faithful reproduction of your sound.

## Main Features

- ✓ True audio reproduction
- ✓ Improved bandwidth
- ✓ 600ohm line level driven output
- ✓ Earth (Ground) lift
- ✓ Left/Right XLR output connectors as standard
- ✓ For live events audio
- ✓ USB powered
- ✓ Compact size

## 3 Year Limited Factory Warranty

### Specifications:

#### Signals:

Typical USB input  
Bandwidth: 20Hz to 20KHz signal levels

#### Control Switches:

Earth (Ground) lift  
Stereo to Mono

#### Connections:

USB input  
Output: 2 male XLR

#### Dimensions mm (inch):

DxWxH: 71(2 <sup>4</sup>/<sub>5</sub>)x 64(2 <sup>1</sup>/<sub>2</sub>)x 40(1 <sup>3</sup>/<sub>5</sub>)  
Supplied USB input cable

#### Weight:

218g / 8oz

#### Power:

USB powered

Interspace Industries

Unit 7 Polaris Centre, 41 Brownfields, Welwyn Garden City, Hertfordshire, AL7 1AN, UK

call: +44 (0) 1462 600 101

email: [moreinfo@interspaceind.com](mailto:moreinfo@interspaceind.com)

web: [www.interspaceind.com](http://www.interspaceind.com)



## The USB 'Hum' Eliminator

